

STP 50/50 Extended Life Antifreeze/Coolant

SECTION 1. IDENTIFICATION

Product Identifier	STP 50/50 Extended Life Antifreeze/Coolant
Other Means of Identification	36-384STPEXP
Recommended Use	Please refer to Product label.
Restrictions on Use	None known.
Manufacturer / Supplier	Recochem Inc., 850 Montee de Liesse, Montreal, QC, H4T 1P4, Compliance and Regulatory Department, 905-878-5544, www.recochem.com
Emergency Phone No.	CANUTEC, 613-996-6666, 24 Hours
SDS No.	1244

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Acute toxicity (Oral) - Category 4; Specific target organ toxicity (repeated exposure) - Category 2

GHS Label Elements



Signal Word:
Warning

Hazard Statement(s):

H302 Harmful if swallowed.

H373 May cause damage to organs (kidneys) through prolonged or repeated exposure if inhaled, following skin contact and/or if swallowed.

Prevention:

P260 Do not breathe fume, mist, vapours, spray.
P264 Wash hands and skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.

Response:

P301 + P312 IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell.
P330 Rinse mouth.
P314 Get medical advice/attention if you feel unwell.

Storage:

Store in a well ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Product Identifier: STP 50/50 Extended Life Antifreeze/Coolant
SDS No.: 1244
Date of Preparation: May 07, 2015

Disposal:
Dispose of contents/container in accordance with applicable regional, national and local laws and regulations.

Other Hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture:

Chemical Name	CAS No.	%	Other Identifiers
Ethylene glycol	107-21-1	40-70	

Notes

The specific chemical identity and/or exact percentage of composition (concentration) has been withheld as a trade secret.

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

Remove source of exposure or move to fresh air. Call a Poison Centre or doctor if you feel unwell or are concerned.

Skin Contact

Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Wash gently and thoroughly with lukewarm, gently flowing water and mild soap for 5 minutes. Call a Poison Centre or doctor if you feel unwell or are concerned. Clean clothing, shoes and leather goods.

Eye Contact

If eye irritation persists, get medical advice/attention. Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open.

Ingestion

Rinse mouth with water. Call a Poison Centre or doctor if you feel unwell or are concerned.

Most Important Symptoms and Effects, Acute and Delayed

If swallowed: There are 3 stages of effects, which can overlap. Early symptoms can include upset stomach, slurred speech, clumsiness, drowsiness, and convulsions. Second stage symptoms can include rapid heartbeat and breathing, bluish lips and skin, fluid in the lungs and heart failure. In the last stage, there can be kidney stones and kidney damage with lower back pain, and increased then decreased urine production. There may be delayed nervous system effects such as paralysis of the face, clumsiness, impaired hearing and blurred vision. Death can occur at any stage.

Immediate Medical Attention and Special Treatment

Target Organs

Digestive system, nervous system, heart, digestive system, kidneys, skin.

Special Instructions

The signs and symptoms in ethylene glycol poisoning are those of metabolic acidosis, central nervous system depression and kidney injury. Clinical chemistry may reveal anion-gap metabolic acidosis and uremia. Treatment with ethanol to inhibit the metabolism of glycol to oxalate. Early administration of ethanol may counter the toxic effects of ethylene glycol (cardiopulmonary effects attributed to metabolic acidosis and renal damage).

Hemodialysis or peritoneal dialysis have been of benefit. Pre-existing respiratory and skin disorders may be aggravated by over-exposure to this product. Treat symptomatically and supportively.

Medical Conditions Aggravated by Exposure

Dermatitis.

SECTION 5. FIRE-FIGHTING MEASURES

Product Identifier: STP 50/50 Extended Life Antifreeze/Coolant

SDS No.: 1244

Page 02 of 08

Date of Preparation: May 07, 2015

Extinguishing Media

Suitable Extinguishing Media

Carbon dioxide, dry chemical powder or appropriate foam.

Unsuitable Extinguishing Media

None known.

Specific Hazards Arising from the Chemical

Can ignite if strongly heated.

In a fire, the following hazardous materials may be generated: irritating chemicals.

Special Protective Equipment and Precautions for Fire-fighters

Review Section 6 (Accidental Release Measures) for important information on responding to leaks/spills.

See Skin Protection in Section 8 (Exposure Controls/Personal Protection) for advice on suitable chemical protective materials.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Use the personal protective equipment recommended in Section 8 of this safety data sheet.

Environmental Precautions

Do not allow into any sewer, on the ground or into any waterway.

Methods and Materials for Containment and Cleaning Up

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Conditions for Safe Storage

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Product Identifier: STP 50/50 Extended Life Antifreeze/Coolant
SDS No.: 1244
Date of Preparation: May 07, 2015

Control Parameters

Chemical Name	ACGIH TLV®		OSHA PEL		AIHA WEEL	
	TWA	STEL	TWA	Ceiling	8-hr TWA	TWA
Ethylene glycol	10 mg/m3	100 mg/m3	Not established	50 ppm		

Appropriate Engineering Controls

The hazard potential of this product is relatively low. General ventilation is usually adequate. Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air.

Individual Protection Measures

Eye/Face Protection

Not required but it is good practice to wear safety glasses or chemical safety goggles.

Skin Protection

Wear chemical protective clothing e.g. gloves, aprons, boots.
Nitrile rubber.

Respiratory Protection

Not normally required if product is used as directed. For non-routine or emergency situations: wear a NIOSH approved air-purifying respirator with an appropriate cartridge.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties

Appearance	Clear orange liquid.
Odour	Odourless
Odour Threshold	Not available
pH	7.8 - 8.6 (100% solution)
Melting Point/Freezing Point	-37 °C (-35 °F) (melting); -37 °C (-35 °F) (freezing)
Initial Boiling Point/Range	129 °C (264 °F)
Flash Point	Not available
Evaporation Rate	Not available
Flammability (solid, gas)	Not applicable
Upper/Lower Flammability or Explosive Limit	Not available (upper); Not available (lower)
Vapour Pressure	Not available
Vapour Density (air = 1)	Not available
Relative Density (water = 1)	1.06 - 1.09 at 20 °C
Solubility	Not available in water; Soluble in all proportions in ketones (e.g. acetone).
Partition Coefficient, n-Octanol/Water (Log Kow)	Not available
Auto-ignition Temperature	Not available
Decomposition Temperature	Not available
Viscosity	Not available (kinematic); Not available (dynamic)
Other Information	
Physical State	Liquid
Molecular Weight	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Product Identifier: STP 50/50 Extended Life Antifreeze/Coolant
SDS No.: 1244
Date of Preparation: May 07, 2015

Not reactive under normal conditions of use.

Chemical Stability

Normally stable.

Possibility of Hazardous Reactions

None known.

Conditions to Avoid

None known.

Incompatible Materials

Slightly reactive or incompatible with the following materials: oxidizing agents (e.g. peroxides), strong acids (e.g. hydrochloric acid), strong bases (e.g. sodium hydroxide).

Not corrosive to metals.

Hazardous Decomposition Products

None known.

SECTION 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure

Skin contact; ingestion.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Ethylene glycol	2725 mg/m ³ (rat) (4-hour exposure)	4700 mg/kg (rat)	9530 mg/kg (rabbit)

LC50: Not applicable.

LD50 (oral): Not applicable.

LD50 (dermal): Not applicable.

Skin Corrosion/Irritation

May cause moderate or severe irritation based on information for closely related materials. Symptoms include pain, redness, and swelling.

Serious Eye Damage/Irritation

May cause serious eye irritation based on information for closely related materials. Symptoms include sore, red eyes, and tearing.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

At high concentrations vapour may cause lung injury, nose and throat irritation. Symptoms may include coughing, shortness of breath, difficult breathing and tightness in the chest. Symptoms may include headache, nausea, dizziness, drowsiness and confusion.

Skin Absorption

At high concentrations may cause Symptoms may include redness, rash, swelling and itching.

Ingestion

Toxic, can cause death based on information for closely related materials. depression of the central nervous system, and effects on the heart and kidneys. In some cases, there may be delayed effects on the nervous system. There are 3 stages of effects, which can overlap. Early symptoms can include upset stomach, slurred speech, clumsiness, drowsiness, and convulsions. Second stage symptoms can include rapid heartbeat and breathing, bluish lips and skin, fluid in the lungs and heart failure. In the last stage, there can be kidney stones and kidney damage with lower back pain, and increased then decreased urine production. There may be delayed nervous system effects such as paralysis of the face, clumsiness, impaired hearing and blurred vision. Death can occur at any stage.

Aspiration Hazard

Not known to be an aspiration hazard.

Product Identifier: STP 50/50 Extended Life Antifreeze/Coolant

SDS No.: 1244

Date of Preparation: May 07, 2015

STOT (Specific Target Organ Toxicity) - Repeated Exposure

May cause dermatitis. Symptoms may include dry, red, cracked skin (dermatitis).
 May cause Following skin contact and/or if swallowed: harmful effects on the kidneys.

Respiratory and/or Skin Sensitization

Not known to be a respiratory sensitizer. Not known to be a skin sensitizer.

Carcinogenicity

Chemical Name	IARC	ACGIH®	NTP	OSHA
Ethylene glycol	Not Listed	A4	Not Listed	Not Listed

Reproductive Toxicity**Development of Offspring**

If swallowed: at high concentrations animal studies show effects on the offspring. Known to cause: decreased weight. Embryotoxic (late resorptions) teratogenic(external, soft tissue and skeletal defects).

Sexual Function and Fertility

Does not cause effects on sexual function or fertility.

Effects on or via Lactation

No information was located.

Germ Cell Mutagenicity

Not known to be a mutagen.

Interactive Effects

No information was located.

Other Information

TOXIC SUBSTANCE: KEEP AWAY FROM ANIMALS AND SMALL CHILDREN.

SECTION 12. ECOLOGICAL INFORMATION**Toxicity****Acute Aquatic Toxicity**

Chemical Name	LC50 Fish	EC50 Crustacea	ErC50 Aquatic Plants	ErC50 Algae
Ethylene glycol	18500 mg/L (Oncorhynchus mykiss (rainbow trout); 96-hour; fresh water)	74000 mg/L (Daphnia magna (water flea); 24 hr)		

Chronic Aquatic Toxicity

Chemical Name	NOEC Fish	EC50 Fish	NOEC Crustacea	EC50 Crustacea
Ethylene glycol	39140 mg/L (Oncorhynchus mykiss (rainbow trout))		24000 mg/L (Daphnia magna (water flea))	

Persistence and Degradability

No information was located.

Bioaccumulative Potential

This product and its degradation products are not expected to bioaccumulate.

Mobility in Soil

No information was located.

Other Adverse Effects

Product Identifier: STP 50/50 Extended Life Antifreeze/Coolant
 SDS No.: 1244
 Date of Preparation: May 07, 2015

There is no information available.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14. TRANSPORT INFORMATION

Not regulated under Canadian TDG Regulations.

Regulation	UN No.	Proper Shipping Name	Transport Hazard Class(es)	Packing Group
US DOT	3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID (Ethylene glycol)	9	III

Special Precautions for User Please note: In single containers of 5000 lbs capacity or less this product is exempt from DOT regulations (non regulated). Does not require label or placards. Regulated Quantity (RQ)= 5000 lbs (2268 kg) (as ethylene glycol) For bulk shipments equal to or greater than Regulated Quantity (RQ), please adhere to classification as outlined in DOT Classification section.

Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

Canada

Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)

All ingredients are listed on the DSL/NDSL.

USA

Toxic Substances Control Act (TSCA) Section 8(b)

All ingredients are listed on the TSCA Inventory.

SECTION 16. OTHER INFORMATION

SDS Prepared By Compliance and Regulatory Department

Phone No. 905-878-5544

Date of Preparation May 07, 2015

Additional Information We are committed to uphold the Industry Consumer Ingredient Communication Voluntary Initiative.
Please send us your request by visiting our website at www.recochem.com.

Ingredients present (intentionally added ingredients) at a concentration of greater than one percent (1%) shall be listed in descending order of predominance. Ingredients present at a concentration of not more than one percent shall be listed but may be disclosed without respect to order of predominance.

Disclaimer

Notice to reader: To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final

Product Identifier: STP 50/50 Extended Life Antifreeze/Coolant

SDS No.: 1244

Date of Preparation: May 07, 2015

determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Product Identifier: STP 50/50 Extended Life Antifreeze/Coolant
SDS No.: 1244
Date of Preparation: May 07, 2015

Page 08 of 08