



SDS DOCUMENT

1. Chemical Product and Company Identification

Trade Name of this Product: Charcoal Lighter Fluid

SDS ID 8-93794-00138

Chemical Family: PETROLEUM HYDROCARBON OIL


Manufacturer

RPP Products, Inc.

219 S Riverside Ave.

Rialto, CA 92376

www.rppproducts.com



2. Composition and Information on Ingredients

Ingredient	CAS Numbe	Weight %	ACGIH TLV	PEL	STEL
Hydrotreated Light Distilates (petroleum)	64742-47-8	100 %			

3. Hazard Identification

EMERGENCY OVERVIEW

- * Warning: Combustible Liquid and Vapor.
- *This product is a clear, hydrocarbon liquid.
- *It has a solvent petroleum odor. The product floats on water.
- *The Flash Point is > 100 degrees F.
- * Keep away from heat, sparks, and flame.
- *When burned the product produces carbon monoxide and other asphyxiants during combustion.
- *Avoid breathing vapor. Harmful if inhaled and may cause delayed lung injury.
- *Aspiration hazard if swallowed- can enter lungs and cause damage.
- * Use ventilation adequate to keep vapor below recommended exposure limits.
- * Avoid contact with eyes, skin and clothing. Material splashed into the eyes will irritate tissues. Gently flush material from eyes with clean water.
- * Unprotected exposure to this product will cause skin dryness.
- * Remove product soaked clothing and wash with mild soap. Wash thoroughly after handling.
- * As with any petroleum product, avoid mixing this product with strong oxidizers.
- * This product may be toxic to fish but will be toxic to birds and wildlife through ingestion during pelage cleaning.
- * This product is readily biodegradable in the presence of air and sunlight.
- * Spilled material is slippery and may cause falls.

***** END OF EMERGENCY OVERVIEW*****

POTENTIAL HEALTH EFFECTS
PRIMARY ROUTE(S) OF ENTRY
Skin.

EYES
Tests on similar materials suggest acute irritation be expected.

SKIN
Tests on similar materials indicate acute irritation is expected to occur upon short-term exposure, chronic dermatitis on prolonged contact.

INGESTION
ACUTE ASPIRATION HAZARD. Tests on similar materials indicate possibility of the following symptoms: headache, nausea, drowsiness, fatigue, pneumonitis, pulmonary edema, central nervous system depression, convulsions, and loss of consciousness.

INHALATION
Tests on similar material indicate the possibility of the following symptoms: headache, nasal and respiratory irritation, nausea, drowsiness, breathlessness, fatigue, central nervous system depression, convulsions, and loss of consciousness.

CHRONIC (CANCER INFORMATION)
Prolonged and/or repeated contact with this material may produce skin irritation and inflammation.
Carcinogen listed by:
National Toxicology Program (NO)
I. A. R. C. (NO)
OSHA (NO)
ACGIH (NO)

This product does not require a cancer hazard warning in accordance with the OSHA Hazard Communication Standard.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

4. First Aid Information

EYES
Flush eyes immediately with water for at least 15 minutes or until irritation subsides, occasionally lifting lower and upper lids. Get medical attention promptly.

SKIN
Wash thoroughly with soap and water. Immediately remove contaminated clothing and wash before reuse. If irritation or rash develops, obtain medical assistance. Immediately remove soaked clothing.

INGESTION
CALL PHYSICIAN IMMEDIATELY. Do not induce vomiting except at the instruction of a physician. Never give anything by mouth to an unconscious person.

INHALATION
Remove patient to fresh air and consult a physician. If breathing is difficult, give oxygen. If not breathing give artificial respiration.

5. Fire Fighting Measures

Flammable Properties

Flash Point >	430 F
FP Method	COC
FLASH POINT:	> 100 F
TEST METHOD:	Tag Closed Cup.
AUTOIGNITION TEMPERATURE	>600F >316C
FLAMMABILITY CLASS:	II
LOWER EXPLOSIVE LIMIT (%):	not available on test sample
UPPER EXPLOSIVE LIMIT (%):	not available on test sample

FIRE AND EXPLOSION HAZARD

Material is combustible

EXTINGUISHING MEDIA:

USE DRY CHEMICAL, FOAM, OR CARBON DIOXIDE. CAUTION: Water stream may spread fire.

FIRE FIGHTING INSTRUCTIONS:

Use water spray only to cool containers exposed to flames. Do not enter enclosed or a confined work space without proper protective equipment. Fire fighting personnel should wear respiratory protective (positive pressure if available). If leak or spill has not ignited, use water spray to disperse the vapors. Products of combustion include fumes, smoke and carbon monoxide.

UNUSUAL FIRE AND EXPLOSIVE CONDITIONS:

DENSE SMOKE MAY BE GENERATED WHILE BURNING. CARBON MONOXIDE, CARBON DIOXIDE, AND OTHER OXIDES MAY BE GENERATED AS PRODUCTS OF COMBUSTION.

6. Accidental Release Measures

NOTIFICATION PROCEDURES:

Notify emergency response personnel. Evacuate area and remove ignition sources. Build dike to contain flow. Remove free liquid. Shut off ignition source. Report spills as required to appropriate authorities. U.S. Coast Guard regulations require immediate reporting of spills that could reach any waterway including intermittent dry creeks. Report spill to Coast Guard toll free number (800) 424-8802. In case of accident or road spill notify CHEMTRIC (800) 424-9300.

PROCEDURES IF MATERIAL IS RELEASED OR SPILLED:

Absorb on inert material. Shovel up and dispose of at an appropriate waste disposal facility in accordance with current applicable laws and regulations, and product characteristics at time of disposal.

ENVIRONMENTAL PRECAUTIONS: Prevent spills from entering storm sewers or drains and contact with soil.

PERSONAL PRECAUTIONS: See Section 8.

7. Handling and Storage

HANDLING AND STORAGE PRECAUTIONS

Store as OSHA Class II combustible liquid. Keep away from flames, sparks or hot surfaces. Never use a torch to cut or weld on or near container. Empty oil containers can contain explosive vapors. Wash thoroughly after handling. Do not store with strong oxidizers.

STORAGE PRECAUTIONS

Empty containers retain product residue (liquid and vapor) and can be dangerous.
Storage Temperature: ambient.
Storage Pressure: atmospheric.

WORK/HYGIENIC PRACTICES

Wash hands with soap and water before eating, drinking, smoking or use of toilet facilities. Do not use gasoline, solvents, kerosene, or harsh abrasive skin cleaners for washing exposed skin areas. Take a shower after work if general contact occurs. Remove oil-soaked clothing and launder before reuse. Launder or discard contaminated shoes and leather gloves.

“EMPTY” CONTAINER WARNING

“Empty” containers retain residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

Do not attempt to refill or clean containers since residue is difficult to remove. “Empty” drums should be completely drained, properly bunged and promptly returned to a drum reconditioner. All other containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

For work on tanks refer to Occupational Safety and Health Administration regulations, ANSI Z49.1, and other governmental and industrial references pertaining to cleaning, repairing, welding, or other contemplated operations.

8. Exposure Control/Personal Protection

ENGINEERING CONTROLS

Use adequate ventilation to keep oil mists of this material below applicable standard(s). See Section on occupational exposure limits.

EYE/FACE PROTECTION:

Use safety glasses or splash goggles when eye contact may occur. Have suitable eye wash water available.

SKIN PROTECTION:

Avoid prolonged and/or repeated skin contact. If prolonged contact cannot be avoided, wear protective impervious clothing (gloves, boots, aprons, etc.). Acceptable materials for gloves are neoprene; nitrile; and viton.

OTHER/GENERAL PROTECTION

If there is a likelihood of splashing, an oil resistant clothing should be worn. Never wear oil soaked clothing. Launder or dry clean before wearing. Discard oil soaked shoes. Affix warning labels on containers in accordance with 29 CFR 1910.1200 (Hazard Communication Standard).

Loading, unloading, tank guaging, etc., remain upwind. Request assistance of safety and industrial hygiene personnel to determine air concentrations.

INGREDIENT NAME, CAS #, EXPOSURE LIMITS, PERCENT BY VOLUME

Hydrotreated Light Distillate, CAS NUMBER: 64742-47-8, n/av., 100.0

OTHER:

Consumption of food and beverage should be avoided in work areas where hydrocarbons are present. Always wash hands and face with soap and water before eating, drinking, or smoking. Affix warning labels on containers in accordance with 29 CFR 1910.1200 (Hazard Communication Standard).

INGREDIENTS:

HAZARDOUS

COMPONENT NAME IN PERCENTAGE COMPONENT

CAS NUMBER BLEND MIN MAX EXPOSURE LIMIT UNIT

HEAVY PARAFFINIC SOLVENT DEWAXED DISTILLATE 100.0

CAS NUMBER: 64742-65-0

Exposure Limits: OIL MIST

OSHA PEL MIST 5 MG/M3 8 HRS

9. Physical and Chemical Properties

Product CAS Number 64742-54-7

APPEARANCE

Clear liquid

ODOR: Petroleum Naphtha.

ODOR THRESHOLD

N.D.

BASIC PHYSICAL PROPERTIES

PHYSICAL STATE:	Liquid
BOILING POINT:	IBP >310°F
MELTING POINT:	POUR POINT N/A F
VAPOR PRESSURE:	6mm Hg @ 100°F
VAPOR DENSITY (AIR=1):	N/A
SPECIFIC GRAVITY:	0.75 Water = 1
MOLECULAR WEIGHT:	N/A
PACKING DENSITY:	N/A
SOLUBILITY (H2O):	negligible in water
PERCENT VOLATILES:	nil
VOLATILE ORGANIC COMPOUNDS (VOC) CONTENT:	N/A
EVAPORATION RATE:	N/A
pH:	N/A

10. Stability and Reactivity

STABILITY: Stable under normal conditins.

CONDITIONS TO AVOID

Sources of ignition.

INCOMPATIBLE MATERIALS

Strong oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS

Incomplete combustion may produce carbon monoxide and other asphyxiants.

HAZARDOUS POLYMERIZATION: will not occur

11. Toxicological Information

ACUTE STUDIES

N/A

EYE EFFECTS

Slight irritation on contact.

SKIN EFFECTS

May cause irritation or dermatitis with prolonged and repeated contact.

ACUTE ORAL EFFECTS

Tests on similar materials indicate an order of acute oral toxicity.

ACUTE INHALATION EFFECTS

Acute toxicity expected on inhalation.

This product is not listed as carcinogenic or a potential carcinogen by the National Toxicology Program, by the I.A.R.C. monographs or by OSHA. Therefore, if the precautions outlined in this bulletin are followed to minimize repeated or prolonged skin contact which could cause irritation, these oils should pose no carcinogenic hazard to humans. Prolonged repeated skin contact with low viscosity materials may defeat the skin resulting in possible irritation and dermatitis. Nevertheless, good industrial hygienic practices are recommended.

12. Ecological Information

If applied to leaves, this product may kill grasses and small plants by interfering with transpiration and respiration. This product is not toxic to fish but may coat gill structures resulting in suffocation if spilled in shallow, running water. Product may be moderately toxic to amphibians by preventing dermal respiration. This product may cause gastrointestinal distress to birds and mammals through ingestion during pelage grooming.

This product is rapidly biodegradable. Biodegradation is possible within 90 to 120 days in aerobic environments at temperatures above 70 F.

13. Disposal Considerations

WASTE DISPOSAL METHOD:

All disposals must comply with federal, state, and local regulations. Product as supplied does not meet the characteristics of a hazardous waste as defined in 40 CFR 261.21-24. If mixed with other products, waste mixture must be characterized. DO NOT dispose of this product in drains or storm sewers. DO NOT dispose of this product in a landfill without prior solidification. Department of Transportation (DOT) Regulations may apply for transporting this material when spilled. Materials should be recycled if possible. Consider waste brokering.

14. Transportation Information

PROPER SHIPPING NAME: Petroleum Distillates, nos, Class 3, UN 1268, PG III
HAZARD CLASS: Class 3 Flammable Liquid
DOT IDENTIFICATION NUMBER: UN1268
DOT SHIPPING LABEL: DOT Hazardous Material

15. Regulatory Information

U.S. FEDERAL REGULATORY INFORMATION

SARA 302 Threshold Planning Quantity: NOT APPLICABLE

SARA 304 Reportable Quantity : NOT APPLICABLE

SARA 311 Categories: Immediate (Acute) Health Effects --N

Delayed (Chronic) Health Effects --Y

Fire Hazard --N

Sudden Release of Pressure Hazard--N

Reactivity Hazard --N

EPA/TSCA Inventory: The components of this product are listed on the EPA/TSCA inventory of chemicals.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA): No chemicals in this product are subject to the reporting requirements of CERCLA.

SARA TITLE III - SECTION 313 SUPPLIER NOTIFICATION

No chemicals in this product exceed the De Minimus reporting level established by SARA Title III, Section 313 and 40 CFR 372.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA): No chemicals in this product are subject to the reporting requirements of CERCLA Section 101(14)(F). When this product is used in a mixture, or as an ingredient in another product, or in a manufacturing operation, the petroleum exclusion may terminate and an accidental spill may require reporting to the National Response Center.

CANADIAN REGULATORY INFORMATION

The components of this product are/are not listed on the Canadian (DSL) Domestic Substances List.

EUROPEAN (ECC) REGULATORY INFORMATION

This product is listed on the European Inventory of Existing Commercial Substances. EINECS#

16. Other Information

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

The information contained herein is based upon data believed to be reliable and reflects our best professional judgment. Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein and assume no responsibility regarding the suitability of this information for the user's intended purpose or for the consequence of its use. Each individual should make a determination as to the suitability of the information for his/her particular purpose(s).