



SAFETY DATA SHEET

1. Product And Company Identification

SDS ID: SDS 758
 PRODUCT NAME: Prestone® All Season 3-1 Low VOC Windshield Washer Fluid
 PRODUCT NUMBER: AS658P, AS-658P/F
 FORMULA NUMBER: 2717-63C, 2717-86

PRODUCT NOT FOR SALE IN CALIFORNIA

MANUFACTURER: Prestone Products Corporation 69 Eagle Rd. Danbury, CT 06810	CANADIAN OFFICE: AutoSupply Acquisition Canada Inc. 33 MacIntosh Blvd. Concord, ON L4K 4L5	MEXICO OFFICE: ASG Operations Mexico S. de R.L. de C.V. Carretera Mexico Cuautitlan, Kilometro 31.5, Nave Industrial 5, Loma Bonita, Cuautitlan, Mexico, 54800
--	--	--

MEDICAL EMERGENCIES AND ALL OTHER INFORMATION PHONE NUMBER:

(888)269-0750 (in the US and Canada)
 01-800-715-4135 (in Mexico)

TRANSPORTATION EMERGENCY PHONE NUMBER (Chemical Spills and Transport Accidents only):

CHEMTREC 1-800-424-9300 (in the US and Canada) +1 703 741-5970 (outside the US and Canada)

PRODUCT USE: Automobile windshield cleaner/deicer - consumer product


RESTRICTIONS ON USE: None identified

2. Hazards Identification

GHS/HAZCOM 2012 Classification:

Health	Physical
Acute Toxicity Category 4 (inhalation, oral, dermal) Specific Target Organ Toxicity – Single Exposure Category 1	Flammable Liquid Category 3

Label Elements



DANGER!
 Flammable liquid and vapor.
 Harmful if swallowed, in contact with skin and if inhaled.
 Causes damage to eyes and central nervous system.

Prevention:
 P210 Keep away from heat, sparks, open flames, and hot surfaces. No smoking.
 P233 Keep container tightly closed.
 P240 Ground and bond container and receiving equipment
 P241 Use explosion-proof electrical, ventilating, and lighting equipment.



- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe mists, vapors or spray.
- P264 Wash thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves, protective clothing and eye protection.

Response:

- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
- P312 Call a POISON CENTER or doctor if you feel unwell.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P312 Call a POISON CENTER or doctor if you feel unwell.
- P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor.
- P330 Rinse mouth.
- P308+P311 IF exposed or concerned: Call a POISON CENTER, or doctor.
- P370+P378 In case of fire: Use water fog, carbon dioxide, alcohol foam or dry chemical to extinguish.

Storage:

- P403+P235+P233 Store in a well-ventilated place. Keep cool. Keep container tightly closed.
- P405 Store locked up.

Disposal:

- P501 Dispose of contents and container in accordance with local and national regulations.

3. Composition/Information on Ingredients

Component	CAS No.	Amount
Non-hazardous Ingredient	Proprietary	60-90%
Methyl Alcohol (Methanol)	67-56-1	10-<24%

The specific identity and/or exact concentration has been withheld as a trade secret.

4. First Aid Measures

INHALATION: Remove the victim to fresh air. If breathing has stopped administer artificial respiration. If breathing is difficult, have medical personnel administer oxygen. Get medical attention.

SKIN CONTACT: Remove contaminated clothing. Immediately wash contacted area thoroughly with soap and water. If irritation persists, get medical attention.

EYE CONTACT: Immediately flush eyes with large amounts of water. Get medical attention if irritation persists.

INGESTION: Seek immediate medical attention. Immediately call local poison control center or go to an emergency department. Never give anything by mouth to or induce vomiting in an unconscious or drowsy person.

MOST IMPORTANT SYMPTOMS: Inhalation may cause headache, dizziness, drowsiness, nausea, visual impairment, narcosis and unconsciousness. Toxic if swallowed, inhaled or absorbed through the skin. May cause gastrointestinal pain, nausea and vomiting. Ingestion, inhalation or absorption of methanol through the skin may cause central nervous system effects and damage to the optic nerve. Poisonous if swallowed.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT, IF NEEDED: Seek immediate medical attention for ingestion; or prolonged or excessive dermal exposures.



NOTES TO PHYSICIAN: The combination of visual disturbances, metabolic acidosis and an osmol gap is evidence of methanol poisoning. Ethanol is antidotal and its early administration may block the formation of toxic metabolites of methanol. The principal toxic effects of ethylene glycol, when swallowed, are kidney damage and metabolic acidosis. The combination of metabolic acidosis, an osmol gap and oxalate crystals in the urine is evidence of ethylene glycol poisoning. Ethanol is antidotal and its early administration may block the formation of nephrotoxic metabolites of ethylene glycol in the liver. . The objective is to rapidly achieve and maintain a blood ethanol level of approximately 100 mg/dl by giving a loading dose of ethanol followed by a maintenance dose. Intravenous administration of ethanol is the preferred route. Ethanol blood levels should be checked frequently. Hemodialysis may be required.

4-Methyl pyrazole (Fomepizole(R)), a potent inhibitor of alcohol dehydrogenase, has been used therapeutically to decrease the metabolic consequences of methanol and ethylene glycol poisoning. Fomepizole is easier to use clinically than ethanol, does not cause CNS depression or hypoglycemia and requires less monitoring than ethanol. Folic acid may also be administered to enhance the metabolism of formic acid, the toxic metabolite of methanol. Additional therapeutic modalities which may decrease the adverse consequences of ethylene glycol metabolism are the administration of both thiamine and pyridoxine.

Pulmonary edema with hypoxia has been described in a number of patients following poisoning with ethylene glycol. Respiratory support with mechanical ventilation may be required.

There may be cranial nerve involvement in the late stages of toxicity from swallowed ethylene glycol. In particular, effects have been reported involving the seventh, eighth and ninth cranial nerves, presenting with bilateral facial paralysis, diminished hearing and dysphagia.

As there are complicated and serious overdoses, we recommend you consult with the toxicologists at your poison control center.

5. Firefighting Measures

SUITABLE EXTINGUISHING MEDIA: Use water fog, carbon dioxide, alcohol foam or dry chemical. Cool fire exposed containers with water.

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL: Flammable liquid. Methanol-water mixtures will burn unless very dilute. Flame is invisible in daylight. Vapors are heavier than air and may flow along surfaces to distant ignition sources and flashback. Burning may produce carbon monoxide and carbon dioxide.

SPECIAL FIRE FIGHTING PROCEDURES: Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing for fires in areas where chemicals are used or stored.

6: Accidental Release Measures

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES: Eliminate all ignition sources. Ventilate area. Wear appropriate protective clothing and equipment (See Section 8).

METHODS AND MATERIALS FOR CONTAINMENT/CLEANUP: Collect with absorbent material and place in a container suitable for flammable waste.

7. Handling and Storage

PRECAUTIONS FOR SAFE HANDLING:

May be fatal or cause blindness if swallowed! Do not swallow. Avoid eye and skin contact. Avoid breathing vapors or mists. Use only with adequate ventilation. Wash exposed skin thoroughly with soap and water after use. Flammable liquid! Keep away from heat, sparks, open flames and all other sources of ignition. Do not smoke during use.



Empty containers retain product residue and may be dangerous. Do not cut, weld, drill, etc. containers, even empty. Do not reuse empty containers unless properly cleaned.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES: Keep away from heat, sparks, open flames and all other sources of ignition. Store in a cool, well-ventilated area.

NFPA CLASSIFICATION: II

8. Exposure Controls / Personal Protection

EXPOSURE GUIDELINES

CHEMICAL	EXPOSURE LIMIT
Non-hazardous Ingredient	None Established PEL/TLV
Methyl Alcohol (Methanol)	200 ppm TWA OSHA PEL 200 ppm TWA ACGIH TLV skin 250 ppm STEL ACGIH TLV

APPROPRIATE ENGINEERING CONTROLS: Use general ventilation or local exhaust as required to maintain exposures below the occupational exposure limits.

RESPIRATORY PROTECTION: For operations where the exposure limit is exceeded a NIOSH approved supplied air respirator or positive pressure self-contained breathing apparatus is recommended. Organic vapor cartridge respirators are not recommended for methanol vapor exposures. Equipment selection depends on contaminant type and concentration. Select and use in accordance with 29 CFR 1910.134 and good industrial hygiene practice. For firefighting, use self-contained breathing apparatus.

GLOVES: Chemical resistant gloves such as butyl rubber or Viton where contact is possible.

EYE PROTECTION: Splash proof goggles are recommended to prevent eye contact.

OTHER PROTECTIVE EQUIPMENT/CLOTHING: Appropriate protective clothing as needed to minimize skin contact.

9. Physical and Chemical Properties
--

APPEARANCE:	Clear orange liquid	ODOR:	Citrus
ODOR THRESHOLD:	160 - 690 ppm (Methanol)	pH:	10.8
MELTING/FREEZING POINT:	< -1.3°F (< -18.5°C)	BOILING POINT/RANGE:	187.1°F (86.2°C)
FLASH POINT:	105°F (40.6°C) Setaflash	EVAPORATION RATE:	Not determined
FLAMMABILITY (SOLID, GAS)	Not applicable	(Butyl Acetate = 1)	
VAPOR PRESSURE:	96 mmHg @ 20°C	FLAMMABILITY LIMITS:	LEL: 6.0% (Methanol) UEL: 36% (Methanol)
RELATIVE DENSITY:	0.96	VAPOR DENSITY (air = 1):	>1
PARTITION COEFFICIENT (n-octanol/water)	Not determined	SOLUBILITIES	Water: 100%
DECOMPOSITION TEMPERATURE:	Not determined	AUTOIGNITION TEMPERATURE:	Not determined
		VISCOSITY: Cst at 100°C	~ 1



10. Stability and Reactivity

REACTIVITY: Normally unreactive

CHEMICAL STABILITY: Stable

POSSIBILITY OF HAZARDOUS REACTIONS: Reaction with strong oxidizers will generate heat.

CONDITIONS TO AVOID: Heat, sparks, flames and all other sources of ignition.

INCOMPATIBLE MATERIALS: Strong bases, strong acids, strong oxidizing agents and materials reactive with hydroxyl compounds.

HAZARDOUS DECOMPOSITION PRODUCTS: Combustion will produce carbon monoxide, carbon dioxide.

11. Toxicological Information

POTENTIAL HEALTH EFFECTS:

ACUTE HAZARDS:

INHALATION: May cause irritation of the nose and throat. High vapor concentrations may produce nausea, vomiting, headache, dizziness, drowsiness, tingling, numbness and shooting pains in the hands and forearms, and visual disturbances.

SKIN CONTACT: Prolonged contact with the skin may cause redness and defatting of the skin and absorption of harmful amounts of methanol.

EYE CONTACT: Liquid, vapors or mist may cause discomfort in the eye with persistent conjunctivitis, seen as slight excess redness or conjunctiva. Serious corneal injury is not anticipated.

INGESTION: Contains methanol. May cause abdominal discomfort or pain, nausea, vomiting, dizziness, drowsiness, headache, malaise, blurring of vision, irritability, back pain, decrease in urine output, kidney failure, and central nervous system effects, including irregular eye movements, convulsions and coma. Visual effects from methanol include blurred vision, double vision, changes in color perception, restriction of visual fields and complete blindness. Cardiac failure and pulmonary edema may develop.

With massive overdoses of methanol, liver, kidney and heart muscle injury have been described. There may be a delay of 6-12 hours between swallowing methanol and the onset of signs and symptoms. Ingestion of moderate quantities of methanol also produces metabolic acidosis. 60-200 ml of methanol is a fatal dose for most adults. Ingestion of as little as 10 ml may cause blindness.

CHRONIC EFFECTS: Prolonged or repeated inhalation exposure may produce signs of central nervous system involvement, including nausea, vomiting, headache, ringing in the ears, dizziness, vertigo, cloudy and double vision. Prolonged overexposure at levels of 800-1000 ppm may result and in severe eye damage. Prolonged or repeated skin contact may cause skin sensitization and an associated dermatitis in some individuals.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Due to its defatting properties, methanol may aggravate an existing skin condition, e.g., eczema. Due to its liver and kidney injuring potential, the product may exacerbate existing liver and/or kidney diseases.

CARCINOGEN: None of the components of these products is listed as a carcinogen or suspected carcinogen by IARC, NTP, ACGIH or OSHA.



ACUTE TOXICITY VALUES:

Calculated ATE for product: ATE Oral: 416.7 mg/kg
 ATE Dermal: 1250 mg/kg
 ATE Inhalation: 12.5 mg/L

Methanol: LD50 Oral rat 5,628 mg/kg
 LC50 Inhalation rat 64,000 ppm/4 hr.
 LD50 Dermal rabbit 15,800 mg/kg

12. Ecological Information

ECOTOXICITY:
Methanol: LC50 Fathead minnows 29,400 mg/L/96 hr.
 EC50 Daphnia magna >10,000 mg/L/24 hr.

PERSISTENCE AND DEGRADABILITY: Methanol: Readily biodegradable.

BIOACCUMULATIVE POTENTIAL: Methanol: Estimated BCF of 3 - Potential for bioconcentration in aquatic organisms is low.

MOBILITY IN SOIL: Methanol has a very high mobility in soil.

OTHER ADVERSE EFFECTS: None

13. Disposal Considerations

Recycle, incinerate, treat or landfill in accordance with all local, state/provincial and federal regulations.

14. Transport Information

U.S. DOT HAZARD CLASSIFICATION (For Ground Shipments - Non-Bulk (containers with 119 gallons or less only))

PROPER SHIPPING NAME: Excepted From HazMat
TECHNICAL NAME: None
UN NUMBER: None
HAZARD CLASS/PACKING GROUP: Not Applicable
LABELS REQUIRED: None

DOT MARINE POLLUTANTS: This product does not contain Marine Pollutants as defined in 49 CFR 171.8.

IMDG CODE SHIPPING CLASSIFICATION

Shipments with inner packagings 5 L or smaller and gross mass for the package not exceeding 30 kg can be shipped as a Limited Quantity (see below). This product is exempted from marking the UN number (see IMDG Code 3.4.7)

DESCRIPTION: UN1993, Flammable Liquid, n.o.s. (contains Methanol), 3, PG III, FP 40.6 C, Limited Quantities
ID NUMBER: UN1993
HAZARD CLASS: 3
PACKING GROUP: III
LABELS REQUIRED: None
PLACARDS REQUIRED: LIMITED QUANTITIES Mark on Cargo Transport Containers



Shipments with inner packagings greater than 5 L or gross mass for the package exceeds 30 kg:
DESCRIPTION: UN1993, Flammable Liquid, n.o.s. (contains Methanol), 3, PG III, FP 40.6 C
ID NUMBER: UN1993
HAZARD CLASS: 3
PACKING GROUP: III
LABELS REQUIRED: Class
PLACARDS REQUIRED: Class 3

CANADIAN TDG CLASSIFICATION (For Ground Shipments Only)

PROPER SHIPPING NAME: Excepted from Regulation in small means of containment (Section 1.33)
TECHNICAL NAME: None
UN NUMBER: None
HAZARD CLASS/PACKING GROUP: Not Applicable
LABELS REQUIRED: None

IATA/ICAO SHIPPING CLASSIFICATION:
These products are not suitable for shipment by air.

15. Regulatory Information

EPA SARA 311/312 HAZARD CLASSIFICATION: Acute health, chronic health, fire hazard

EPA SARA 313: This Product Contains the Following Chemicals Subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372):

Methanol	67-56-1	10-<24
----------	---------	--------

PROTECTION OF STRATOSPHERIC OZONE: This product is not known to contain or to have been manufactured with ozone depleting substances as defined in 40 CFR Part 82, Appendix A to Subpart A.

CERCLA SECTION 103: Spills of this product over the RQ (reportable quantity) must be reported to the National Response Center. The RQ for the product, based on the RQ for Methanol (<24% maximum) of 5,000 lbs., is 20,833 lbs. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

EPA TSCA INVENTORY: All of the components of this material are listed on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory.

CALIFORNIA PROPOSITION 65: This product contains the following chemicals regulated under California Proposition 65:

Methyl Alcohol (Methanol)	67-56-1	10-<24	developmental
---------------------------	---------	--------	---------------

CALIFORNIA AIR RESOURCE BOARD (CARB) CONSUMER PRODUCT REGULATION: Product not for sale in California.

KOREA: All of the ingredients of this product are listed on the Korean Existing Chemical List (KECL).

16. Other Information

NFPA Rating: Fire: 2 Health: 2 Instability: 0

REVISION SUMMARY: Section 14: Transportation IMDG
SDS Date of Preparation/Revision: January 10, 2017

This SDS is directed to professional users and bulk handlers of the product. Consumer products are labeled in accordance with



Federal Hazardous Substances Act regulations.

While Prestone Products Corporation believes that the data contained herein are factual and the opinions expressed are those of qualified experts regarding the results of tests conducted, the data are not to be taken as a warranty or representation for which Prestone Products Corporation assumes legal responsibility. They are offered for your consideration, investigation and verification. Any use of these data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.